

# Seeflex O20E

- Light weight Seeflex media, specifically designed for load and weigh scale type equipment.
- Seeflex O20E is a clear ether based thermoplastic polyurethane alloy.
- Having no memory Seeflex O20E will not fracture as a result of constant flexing.
- Dust control sleeves and transitions, 1st choice for dust free factories.
- Excellent abrasion resistance.



## Physical Properties

Surface Finish	Gloss/Gloss
Hardness (Shore A)	90
Wall Thickness (+/- 10%)	0.35 mm / 1/64 inch
Tensile Strength (MPa)	78
Operating Temp Range	-25 to 80°C -13 to 176°F
Max. Surge Temp (°C)	100°C / 212°F
Low Temp, Flexibility	Good
Ultimate Elongation (%)	644
Tear Strength – Die C (N)	17
Surface Resistivity (Ohms)*	10 <sup>10</sup>
100% Modulus (MPa)	8.3
300% Modulus (MPa)	18.4
Air Permeability	0

Atex Compliant: IBExU tested. Can be used in all dust explosion hazardous areas.

(Some restrictions apply - a copy of certification is available on request).

Complies with following regulations:

FDA CFR 177.1680 & 177.2600

(EC) 1935/2004, 2023–2006 & 10/2011, USDA & 3A (20-).

\* Tested to ASTM D-257